



Nalfleet 2000 25 L

Product Group: 653

Product number: 777710

General description

Nalfleet 2000 combines film forming corrosion inhibitors with a scale suppressant in liquid form for ease of application. Nalfleet 2000 is soluble in water in all proportions and does not contain chromates.

Features

- Protects all common metals in cooling systems from corrosive attack
- Protects against cavitation erosion
- Compatible with anti-freeze solutions
- Simple to control
- Safe to apply and handle

Benefits

- Minimises sludge and scale deposits
 - Approved by major diesel engine manufacturers
-

Ordering information

Product Number	Product name
777710	NALFLEET 2000 25 LTR

Accessories

Test Kit for Nitrite, Chloride and P Alkalinity.

Product Number	Product name
777066	MOTOR SHIP TEST KIT MO246A.

Directions for use

Nalfleet 2000 has been designed for use in all common types of engine cooling water systems. Nalfleet 2000 will protect ferrous metals, copper and copper alloys and all other metals including aluminium components. Nalfleet 2000 will not affect rubber gaskets or other non-metallic components within the cooling system.

Sampling and Testing

The WSS Nitrite Test Kit (777067) provides the necessary equipment to carry out the control tests. Obtain a representative sample of the cooling water. Carry out the tests immediately after sampling (following the instructions given in the Test Kit) and log the results in Waterproof. The results should be sent to WSS as stated in the Waterproof instructions. It is important that testing is carried out at least once per week, to ensure levels of treatment are correct.

Dosing and Control

Engine cooling systems should be drained, flushed and if necessary, chemically cleaned, to remove old rust and scale deposits before treatment with Nalfleet 2000 can begin.

Nalfleet 2000 is easy to apply as received, and is fully compatible with water in ethylene glycol solutions. It contains an anti-scalant which helps to keep engine systems clean and free from corrosion and scale formation. Nalfleet 2000 maintains design heat transfer efficiencies and extends the life of the engine.

Cases of unusual coolant loss should be checked and remedial action taken. Nalfleet 2000 should be introduced during circulation of the cooling water. Nalfleet 2000 is best added by means of a feeder installed on a by-pass to the circulating system or in smaller systems, it can be added directly to the header tank. Initial treatment is at a rate of 32 liters of Nalfleet 2000 per 1m³ of coolant to give a control level of 700 to 1000ppm nitrite (1000 to 1500ppm as sodium nitrite). Overdosing with Nalfleet 2000 is not harmful to the system. Control by a simple test for nitrite and pH. Refer to table below for guide to dosing.

Nitrite ppm	0	250	500	750	1000
Sodium Nitrite ppm	0	375	750	1125	1500
Nalfleet 2000 ltr/m ³	32	24	16	8	0

Documentation

- [NALFLEET 2000 25 LTR](#)
-

Further Technical Data

Form	Liquid
Colour	Deep red
Density	1.095 - 1.125 kg/lit
pH	ca 11.0
Specific Heat	3.9 J/g.K
Thermal Conductivity	79mS/cm
Viscosity	1.3 cST
Freeze Thaw Recovery	Complete
Materials compatibility	Stainless Steel, PVC, Polypropylene, Polyethylene, Natural Rubber, Synthetic Rubber, Viton
